myOSLautomatic 4.0

Flexible system that grows with your needs

myOSLautomatic 4.0 is an extension of our myOSLraser 4.0 and myOSLirradiator 4.0 allowing full automation of up to 50, 500, or 4000 dosimeters. State-of-the-art components, modern design and a user-friendly operating interface provide an excellent performance.

All myOSLAutomatic feeders are compatible with the myOSLraser 4.0 and myOSLirradiator 4.0 without any modifications allowing the system to expand and grow with the needs of your business.







myOSLautomatic 4.0

Flexible OSL reader that grows with your needs

Specifications

Capacity	50 dosimeters / 1 Magazine (myOSLautomatic 50)
	500 dosimeters / 10 Magazines (myOSLautomatic
	500)
	4000 dosimeters / 80 Magazines in 8 Boxes
	(myOSL4000)
Magazine Dimensions	60 mm x 400 mm x 30 mm (W x D x H)
Weight (Magazine)	120 g (unloaded)
	520 g (loaded)
Dimensions (myOSLautomatic 50)	1100 mm x 480 mm x 420 mm (W x D x H)
Weight (myoSLautomatic 50)	30 kg
Dimensions (myOSLautomatic 500)	1400 mm x 800 mm x 1450 mm (W x D x H)
Weight (myoSLautomatic 500)	230 kg
Dimensions (myOSL4000)	1050 mm x 1750 mm x 2320 mm (W x D x H)
Weight (myOSL4000)	900 kg
Software	OSLdosimetry software running on a separate PC
Data output	LAN to PC, IP device worldwide accessible for
	distance operation remote support
Power supply voltage	100-240 V, 50-60 Hz

Related products

Automation options





myOSLDosimeter 4.0





All information in this brochure is subject to technical changes without notice.